



Concremove

LIQUID SOLUTIONS

RELEASE AGENTS AND PLANT CARE

Concremove is a concrete remover for plant and tools, developed to replace highly corrosive mineral acids. It cleans away dry hardened concrete, efflorescence and tar deposits from most surfaces without damaging or corroding them.

DESCRIPTION

What is Concremove?

Concremove is a concrete remover for plant and tools. It was developed to replace traditional highly corrosive, strong mineral acids, allowing the safe and non-hazardous cleaning and removal of dry hardened concrete, efflorescence and tar deposits from most surfaces without damaging or corroding them.

It is highly efficient at penetrating and loosening concrete, and is also a powerful cleaner and degreaser. Concremove contains no phosphoric or hydrochloric acids, is low odour and non-fuming, low VOC and over 90% biodegradable in 7 days.

APPLICATIONS

- › Plant and tools with hardened concrete deposits
- › Removing cement, tar, efflorescence, rust and limescale
- › Stone, tiles and other porous substrates
- › Glass, rubber and painted surfaces
- › Interior and exterior use

KEY BENEFITS

- ✓ Highly efficient at penetrating and loosening concrete
- ✓ Readily removes cement and tar deposits
- ✓ Effective at removing efflorescence, rust and limescale
- ✓ Non-corrosive on metals and coatings
- ✓ Powerful cleaner and degreaser with no surface damage
- ✓ Contains no phosphoric or hydrochloric acids
- ✓ Low VOC and over 90% biodegradable in 7 days
- ✓ Low odour and non-fuming
- ✓ Safe and non-hazardous



TECHNICAL DATA

Form	Liquid concrete remover
Dilution	Use as supplied, do not dilute
Application	Low pressure hand spray, roller or brush
Reaction time	5 to 30 minutes, depending on deposit thickness
Substrate temperature	5°C to 30°C
Typical coverage	Approximately 5 to 8m² per litre (guidance only)
Acids	Contains no phosphoric or hydrochloric acids
Biodegradability	Over 90% biodegradable in 7 days
VOC	Low VOC
Storage	Dry place, 5°C to 30°C
Shelf life	12 months in sealed containers, use within 2 months of opening

PACKAGING

Contact UKCP for current packaging options.

STORAGE AND SHELF LIFE

12 months in sealed containers from date of manufacture. Must be used within 2 months of opening. Store in a dry place between 5°C and 30°C.

HEALTH AND SAFETY

Refer to the Safety Data Sheet, available on request from UKCP.

APPLICATION AND TECHNICAL SUPPORT

Coverage and performance depend on the surface, conditions and method of application. Contact the UKCP technical team on 07717 707163 or sales@ukconstructionproducts.co.uk for application guidance and advice on product selection. Trial the product on a small area where appropriate. The latest version of this datasheet is available at ukconstructionproducts.co.uk/products/concremove.